



## Specifications Noxion LED Panel Louvre Excell Pronox 38W 4200lm - 840 Cool White | 150x15cm - UGR 152 - Dali Dimmable

[View Product](#)

### General Information

|                      |                                                                      |
|----------------------|----------------------------------------------------------------------|
| SKU                  | 235767                                                               |
| EAN                  | 8719157006590                                                        |
| Manufacturer Code    | 8719157006590                                                        |
| Brand                | Noxion                                                               |
| Manufacturer Name    | Noxion LED Louvre Excell G2. 38W 4000K 1500 Polish DALI (1x49W eqv.) |
| Budgetlight warranty | 6 Years                                                              |
| Average Lifetime (h) | 70000                                                                |
| Product Serie        | Louvre Excell                                                        |

### Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 1x49               |
| Wattage                     | 38W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |

|                        |                                         |
|------------------------|-----------------------------------------|
| Luminous Flux (Lumen)  | 4200lm                                  |
| Lumen per watt         | 110.5                                   |
| Suitable for Outdoor   | No                                      |
| IP-rating              | IP20                                    |
| Impact Protection (IK) | IK02 - 0.20 joule                       |
| Fixture Connection     | Terminal, 2-pole (MAINS)   2-pole (DIM) |
| Finish of Reflector    | Gloss                                   |
| Driver Included        | Yes                                     |
| Power factor           | >0.90                                   |
| Product Type Category  | LED Panel                               |

### Fixture Information

|                       |                                  |
|-----------------------|----------------------------------|
| Mounting Method       | Recessed                         |
| Unified Glare Rating  | < 15 - For specific uses         |
| Optical Cover         | PET (Polyethylene Terephthalate) |
| Operating Temperature | -20 to +50                       |
| Emergency Lighting    | No Emergency Unit                |
| Colour of the Fixture | White                            |
| Housing               | Steel                            |
| Colour of material    | White                            |

### Dimensions

|                |          |
|----------------|----------|
| LED panel size | 150x15cm |
| Length (mm)    | 1495     |
| Width (mm)     | 150      |
| Height (mm)    | 55       |

### Sensor Information

Type of sensor

No Sensor

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**



**Easy** return process



Long-life **LED solutions**